



MidRotoSonic XL MAX

Ask for your
tailored
OPEX ROI
calculation !



MRS XL MAX:

- Mineral sampling
- Environmental exploration
- Geotechnical sampling and testing
- Geo-constructional drilling
- Seismic drilling
- Customized solutions

The MidRotoSonic XL MAX (MRS XL MAX) is upgraded from the reliable CRS XL platform and build to host the powerfull LS 50k Sonic drill-head in a relatively small package. The MRS XL MAX accelerates drill speed, capacity and boosts your productivity.



MidRotoSonic Drill head	Metric	Imperial
Max. frequency	0 - 150 Hz	0 - 150 Hz
Sonic vibration oscillator output force	227 kN	50 k lbf
2 eccentrics, mechannically synchronized		
Rotation torque: clockwise 0-140 rpm	5.605 Nm @ 240 bar	4,134 ft-lbf @ 3,480 psi
Rotation torque: counter clockwise	7.200 Nm @ 310 bar	5,315 ft-lbf @ 4,495 psi
Head tilt max.	90°	90°
Type of damper / buffer	air cushion	air cushion
Max. hydraulic pressure on sonic	310 bar	5,000 psi
Mass of head	1.200 kg	2,700 lbf
Pull up force in combination with sonic	10.000 daN	22,480 lbf
Pull down force in combination with sonic	10.000 daN	22,480 lbf
Pull up force static	10.000 daN	22,480 lbf
Pull down force static	10.000 daN	22,480 lbf
Drilling under angle perpendicular driving direction	10°	10°

Rig	Metric	Imperial
Caterpillar 6 cylinder water cooled engine	205 kW	279 HP
Mass approx.	15.000 kg	33,000 lbs
Fuel tank (diesel)	230 liter	60 gallon
Load sensing hydraulic system	Included	Included
Control panel on turning arm	Included	Included
High pressure water pump	19 l/min. @ 210 bar	5 gpm @ 3,045 psi
Large flow water pump	283 l/min. @ 70 bar	75 gpm @ 1,015 psi
Aluminum water tank	500 liter	132 gallon
Rubber tracks	Included	Included
Radio remote for driving	Included	Included
Work lights	4	4

Mast	Metric	Imperial
Stroke (depending on manipulator)	5200/5500 mm	17'/18'
Mast dump	1000 mm	3' 3 ¹ / ₈ "
Pull up	120 kN	26,977 lbf
Pull down	68 kN	15,287 lbf
Pull up and down speed	45 m/min	147 ft/min
Double hydraulic break out clamp	60 - 355 mm	2 3 ¹ / ₈ " - 13 3 ¹ / ₃₂ "
Adjustable clamping force of	0-140 kN	0-31,473 lbf
Break out torque	54 kNm	39,828 ft-lbf
Hydraulic break out cylinder	Included	Included
Main winch	3600 daN, speed 35 m/min, 30 m cable diam. 14 mm	8,093 ft-lbf, speed 115'/min, 98' cable diam. 0.55"

Rod / casing handler		
Mechanical separators among different rod layers	Included	Included
Casing or drill rod storage depends on diameter and length	Included	Included




Eijkelkamp
 Meet the difference



Options	Metric	Imperial
SPT auto drop hammer with blow counter on control panel		
Casing lifter mounted on break out clamp	200 kN stroke 300 mm	45,000 lbs stroke 12"
Pneumatic separators among different rod layers		
Duplex mud pump	570 liter @ 45 bar	150 gallon @ 652 psi
SPX40 hose pump	114 l/min @ 9.6 bar	30 gpm @ 140 psi
Steel tracks		
Triple floatable clamp		
ManipAll 250 (manual or remote controlled)		
Safety cage		
Rotatable jibboom with second winch		



Eijkelkamp Customer Service Agreement

Royal Eijkelkamp provides the possibility to add a tailor fit service contract to the extensive range of machines we offer. We call these the Eijkelkamp Customer Service Agreements. We have three types of Customer Service Agreements called Start, Pro and Royal. The Royal type is a service contract that can be tailor fit to the needs of the customer. All Eijkelkamp Customer Service Agreements will be delivered with the Eijkelkamp Service Assistant, this is an advanced track & trace system that is available for use by customer and driller on site via the mobile phone application and web browser.

For more information on demos, pilot projects or personal advice contact our sales department !

For urgent service calls and/or technical information contact or special service telephone: +31 313 800 967

ROYAL Eijkelkamp
Meet the difference

Nijverheidsstraat 9
6987 EN Giesbeek
The Netherlands

T +31 313 880 200
E info@eijkelkamp.com
I royaleijkelkamp.com